


Experience 4G LTE Wireless Communication

NO wiring needed, No Wi-Fi issues



4G LTE Video Intercom



Intercom Features:

- ◆ 4G VoIP videocall / 3G mobile voice call
- ◆ AI face detection
- ◆ Support 3000 users
- ◆ Support 1000 RFID 13.56MHz Mifare cards
- ◆ Support 1000 PIN codes
- ◆ 24/7 recording/monitoring
- ◆ 4G LTE/3G/GSM networks
- ◆ HD video surveillance
- ◆ SD card storage up to 128GB
- ◆ Hidden antenna

APP Features:

- Add/delete/modify flat number/phone number/ PINcode/ Mifare card.
- Unlock the door remotely
- Manage multiple devices
- Play video record
- Check call/access log
- Door unlock/lock and offline notifications
- Take screenshot



Applications:

Multi-Tenant 4G video intercom that can be used for apartment buildings, gated communities, residential complex, assisted care centers.

It offers building owners and property managers alike the most versatile, feature-rich intercoms for multi-tenant properties. With our advanced technology, tenants or grounds guards can easily identify entrants before granting them access into the building.



Specifications:

| Model Number | | SS1912 |
|-----------------------|-----------------------|--|
| Video | Image Sensor | 1/2.7" 2MPCMOS |
| | Image Compression | H.265 |
| | Image Frame Rate | 25fps maximum |
| | Resolution | 1080P (1920 x 1080), VGA (720 x 576) |
| | Lens | 2.8 mm |
| | View angle | H:90° V:80° |
| | Day Vision | Color Image, auto switch IR-CUT |
| | Nigh Vision | BW Image, 6 Infrared LED |
| Audio | Audio Input | Omnidirectional Mic |
| | Audio Output | Built-in Speaker |
| | Bidirectional Talk | Dual-way bidirectional talk |
| | Audio Compression | AMR |
| Display | LED digital display | 5-Digit |
| Storage | SD Card | Micro SD,128GB (Max) |
| Network | Ethernet | 10/100Mbps (PoE optional) |
| | Mobile network | 4G LTE/3G WCDMA/2G GSM |
| Call | Video Call | Android and iOS APP |
| | Voice Call | Mobile voice call |
| Door Release | Unlock door | Remotely by APP, mobile voice call DTMF, PIN code, Mifare card |
| | Relay Outputs | 2 |
| | Exit Button input | 1 |
| | Detector input | 1 |
| | Relay type | NO & NC |
| | Relay time | 3,8,15,30,60,300,600 seconds |
| | Relay load | 10A(AC240V/DC24V) |
| Operation Mode | Keypad | Mechanical Button |
| | Reader | Type A Mifare 13.56 MHz Card reader |
| Alarm | Face detection | Record 10s video clip |
| | Notification | Alarm , Warning |
| Power | Power Supply | 12V-24V DC 1.5A |
| | Power Consumption | 10 Watts (Max.) |
| Environment | Operating Temperature | -10 to +50 °C (+14 to +124 °F) |
| | Operating Humidity | 10~80%RH |
| | Storage Temperature | -20°C ~ 60° (-4°F ~ 140°F) |
| | Storage Humidity | 0% ~ 90% |
| General | Reset | Hardware reset button |
| | SIM Card | Micro SIM card |
| | Material | Alum-Alloy + Acrylic |
| | IP Rating | IP65 |
| | Product Dimension | 276(L)*116(W)*50(H) mm |
| | Net Weight | 1.5 Kg |